

-GUILLOTINES > IDEAL 4810-95 EP GUILLOTINE

IDEAL 4810-95 EP GUILLOTINE



Model : -

A3+ ELECTRICAL CUTTING, CLAMPING AND BACK GAUGE

User friendly paper guillotine. Cuts large paper sizes up to 475 mm length. Max. cutting capacity : 80mm. Min. remaining cutting stroke : 30mm. Table depth : 458mm.

Electro-mechanical blade drive. Manual spindle clamp, guided on both sides, with large hand wheel. Power backgauge with fully programmable "EP" backgauge control module and digital display for measurement readout in cm or inches (display accurate to 1/10 mm or 1/100 inch); 10-button key pad for presetting of measurement; memory key for repeat cuts; programmable "EP" backgauge control module for 9 programs with 9 steps in each program (up to 9 repeat cuts can be integrated into a program as one single program step); setting of program steps via "Start" button; "SET" function key for reference measurement; programmable EJECT function - for pushing out the paper; two programmable keys for quick setting of frequently needed measurements; self-diagnosis system with error indication on display. Electronic hand wheel for manual backgauge positioning with infinitely variable speed control (from very slow to very fast). Optical cutting line. Two side lays each on front and rear tables. Solid steel blade carrier and adjustable blade guides. Solid all-metal construction. Complete with stand and storage shelf.

"SCS"-Safety package (Safety Cutting System):

Hinged, electronically controlled safety guards in the working area. Transparent safety cover on the rear table. Main switch and safety lock with key. Electronically controlled true two-hand operation. Patented IDEAL safety drive. Automatic blade and clamp return from every position. 24 volt controls (low voltage). Disc brake for instant blade stop. Blade changing device with covered cutting edge. Blade depth adjustment from the outside of the machine. Safety tested by major independent safety laboratories and complies with the European "CE" standards.

Power supply: 230V 50 Hz / 1~. Motor performance (input capacity): blade drive 1.1 kW, backgauge drive 0.1 kW. Dimensions (HxWxD) : 1360x755x970mm. Weight: 200 kg. Colour: pearl grey.